

# Micro Motion<sup>®</sup> H-Series Hygienic Coriolis Flow and Density Meters



## High accuracy real world performance

- Best-in-class performance on liquid mass flow, volume flow, and density measurements in a compact design
- Superior sensitivity in a compact design to reduce variability in process control
- Rugged design minimizing process, mounting, and environmental effects

## Best fit-for-application

- Cleanable, self-draining design for critical process control service
- Compact design enables installation flexibility
- Broad range of I/O offerings including HART, Profibus-DP, FOUNDATION<sup>™</sup> fieldbus, 4-20mA, and wireless capabilities

## Exceptional reliability and safety

- No moving parts to wear or replace minimizes maintenance for long-term reliability
- 316L stainless steel wetted parts construction with up to a 15 Ra surface finish for hygienic compatibility
- Robust sensor design

**MICRO MOTION**<sup>™</sup>

  
**EMERSON**<sup>™</sup>

## Micro Motion H-Series hygienic flow and density meters

Micro Motion H-Series meters deliver superb measurement with exceptional flow and density performance as well as outstanding reliability in a compact hygienic design for use in sanitary process control environments.

### Tip

If you need help determining which Micro Motion products are right for your application, check out the [Micro Motion® Technical Overview and Specification Summary](#) and other resources available at [www.emerson.com/flowmeasurement](http://www.emerson.com/flowmeasurement).

### Optimal flow and density fit for hygienic process control applications

- High performance rugged measurement in a compact self-draining design
- Low frequency, high sensitivity fit-and-forget meter provides robust measurements even under demanding process conditions
- Multiple line sizes provide an ideal platform for batching, distribution, allocation and intra-plant measurement applications

### Smart Meter Verification: advanced diagnostics for your entire system

- A comprehensive test that can be run locally or from the control room to provide confidence in your meter functionality and performance
- Verifies that your meter performs as well as the day it was installed, giving you assurance in less than 90 seconds
- Save significant expenditure by reducing labor and outsourced calibration service costs while eliminating process interruption

### Industry-leading capabilities that unleash your process potential

- Available with the most extensive offering of transmitter and mounting options for maximum compatibility with your system
- State of the art, ISO/IEC 17025 compliant calibration stands achieving  $\pm 0.014\%$  uncertainty drive best in class measurement accuracy
- The most robust communication protocol offering in the industry including Smart Wireless
- True multi-variable technology measures necessary flow and density process variables simultaneously

### Widest range of installation and process condition flexibility

- Featuring a low pressure drop, low weight design that reduces installation and commissioning costs
- Unmatched MVD transmitter technology with digital signal processing (DSP) delivers the fastest response rates enabling accurate batch and process measurement
- Design flexibility enables operation in SIP, CIP and sanitary where 3-A and EHEDG compliance is required


## Measurement principles

As a practical application of the Coriolis effect, the Coriolis mass flow meter operating principle involves inducing a vibration of the flow tube through which the fluid passes. The vibration, though it is not completely circular, provides the rotating reference frame which gives rise to the Coriolis effect. While specific methods vary according to the design of the flow meter, sensors monitor and analyze changes in frequency, phase shift, and amplitude of the vibrating flow tubes. The changes observed represent the mass flow rate and density of the fluid.

### Mass flow measurement

The measuring tubes are forced to oscillate producing a sine wave. At zero flow, the two tubes vibrate in phase with each other. When flow is introduced, the Coriolis forces cause the tubes to twist resulting in a phase shift. The time difference between the waves is measured and is directly proportional to the mass flow rate.

Watch this video to learn more about how a Coriolis flow meter measures mass flow and density (click the link and select **View Videos**): <https://www.emerson.com/en-us/automation/measurement-instrumentation/flow-measurement/coriolis-flow-meters>.



- A. Inlet pickoff displacement
- B. No flow
- C. Outlet pickoff displacement
- D. Time
- E. Inlet pickoff displacement
- F. With flow
- G. Outlet pickoff displacement
- H. Time difference
- I. Time

## Density measurement

The measuring tubes are vibrated at their natural frequency. A change in the mass of the fluid contained inside the tubes causes a corresponding change to the tube natural frequency. The frequency change of the tube is used to calculate density.

## Temperature measurement

Temperature is a measured variable that is available as an output. The temperature is also used internal to the sensor to compensate for temperature influences on Young’s Modulus of Elasticity.

## Meter characteristics

- Measurement accuracy is a function of fluid mass flow rate independent of operating temperature, pressure, or composition. However, pressure drop through the sensor is dependent upon operating temperature, pressure, and fluid composition.
- Specifications and capabilities vary by model and certain models may have fewer available options. For detailed information regarding performance and capabilities, either contact customer service or refer to [www.emerson.com/flowmeasurement](http://www.emerson.com/flowmeasurement).
- The letter at the end of the base mode code (for example, H100S) represents wetted part material S = 316L stainless steel 32 Ra finish (0.8 μm) and F = 316L stainless steel 15 Ra finish (0.4 μm).

## Performance specifications

### Reference operating conditions

For determining the performance capabilities of our meters, the following conditions were observed/used:

- Water at 68 °F (20.0 °C) to 77 °F (25.0 °C) and 14.5 psig (1.000 barg) to 29 psig (2.00 barg)
- Accuracy based on industry leading accredited calibration stands according to ISO/IEC 17025
- All models have a density range up to 3 g/cm<sup>3</sup> (3,000 kg/m<sup>3</sup>)

### Accuracy and repeatability

#### Accuracy and repeatability on liquids and slurries

Performance Specifications	Calibration code Z	Calibration code 1	Calibration code K <sup>(1)(2)</sup>
Mass flow accuracy <sup>(3)</sup>	±0.15% of rate	±0.10% of rate	±0.10% of rate
Volume flow accuracy <sup>(1)</sup>	±0.15% of rate	±0.15% of rate	±0.10% of rate
Mass flow repeatability	±0.05% of rate		
Volume flow repeatability	±0.075% of rate	±0.075% of rate	±0.05% of rate
Density accuracy	±0.002 g/cm <sup>3</sup> (±2 kg/m <sup>3</sup> )	±0.001 g/cm <sup>3</sup> (±1 kg/m <sup>3</sup> )	±0.0005 g/cm <sup>3</sup> (±0.5 kg/m <sup>3</sup> )
Density repeatability	±0.001 g/cm <sup>3</sup> (±1 kg/m <sup>3</sup> )	±0.0005 g/cm <sup>3</sup> (±0.5 kg/m <sup>3</sup> )	±0.0002 g/cm <sup>3</sup> (±0.2 kg/m <sup>3</sup> )
Temperature accuracy	±1 °C ±0.5% of reading		
Temperature repeatability	±0.2 °C		

(1) Only available with electronics code 0, 1, 2, 3, 4, 5, 6, 7, 8, 9.

(2) Not available with model H025.

(3) Stated flow accuracy includes the combined effects of repeatability, linearity, and hysteresis.

#### Accuracy and repeatability on gases

Performance specification	All models
Mass flow accuracy <sup>(1)</sup>	±0.50% of rate
Mass flow repeatability <sup>(1)</sup>	±0.25% of rate
Temperature accuracy	±1 °C ±0.5% of reading
Temperature repeatability	±0.2 °C

(1) Stated flow accuracy includes the combined effects of repeatability, linearity, and hysteresis

### Liquid flow rates

#### Nominal flow rate

Micro Motion has adopted the term nominal flow rate, which is the flow rate at which water at reference conditions causes approximately 14.5 psig (1 barg) of pressure drop across the meter.

**Mass flow rates for all models**

Model	Nominal line size		Nominal flow rate		Maximum flow rate	
	inch	mm	lb/min	kg/h	lb/min	kg/h
H025	.25 in to .50 in	DN6 to DN13	50	1336	100	2,720
H050	.50 in to 1 in	DN13 to DN25	155	4226	300	8,160
H100	1 in to 2 in	DN25 to DN50	717	19,510	1,200	32,650
H200F	2 in to 3 in	DN50 to DN80	1,917	52,160	2,350	63,960
H200S	2 in to 3 in	DN50 to DN80	1,917	52,160	3,200	87,100
H300	3 in to 4 in	DN80 to DN100	4,900	133,356	8,744	238,499

**Volume flow rates for all models**

Model	Nominal flow rate			Maximum flow rate		
	gal/min	barrels/h	l/h	gal/min	barrels/h	l/h
H025	6	9	1,366	12	18	2,720
H050	19	27	4,226	36	52	8,160
H100	86	123	19,510	144	206	32,650
H200F	230	328	52,160	384	550	87,100
H200S	230	328	52,160	384	550	87,100
H300	587	839	133,356	1,047	1,497	238,499

**Gas flow rates**

When selecting sensors for gas applications, pressure drop through the sensor is dependent upon operating temperature, pressure, and fluid composition. Therefore, when selecting a sensor for any particular gas application, it is highly recommended that each sensor be sized using the Sizing and Selection Tool at [www.emerson.com/flowmeasurement](http://www.emerson.com/flowmeasurement).

The following table indicates flow rates that produce approximately 25 psig (1.72 barg) pressure drop on natural gas.

**Gas flow rates for all models**

Model	Mass		Volume	
	lb/min	kg/h	SCFM	Nm <sup>3</sup> /h
H025	17	468	388	659
H050	52	1,429	1,183	2,010
H100	200	5,452	4,514	7,670
H200	666	18,137	15,018	25,515
H300	1,745	47,505	39,334	66,829

**Note**

- Standard (SCFM) reference conditions are 14.7 psig (1.014 barg) and 60 °F (15.6 °C).
- Normal reference conditions are 14.60 psig (1.0066 barg) and 32 °F (0.0 °C).


- Natural gas with molecular weight of 16.799 at 60 °F (15.6 °C) and 1,014.7 psia (69.961 bara).

## Zero stability

Zero stability is used when the flow rate approaches the low end of the flow range where the meter accuracy begins to deviate from the stated accuracy rating, as depicted in the turndown section. When operating at flow rates where meter accuracy begins to deviate from the stated accuracy rating, accuracy is governed by the formula:  $\text{accuracy} = (\text{zero stability}/\text{flow rate}) \times 100\%$ . Repeatability is similarly affected by low flow conditions.

### Turndown capabilities

The graph and table below represent an example of the measurement characteristics under various flow conditions. At flow rates requiring large turndowns (greater than 20:1), the zero stability values may begin to govern capability dependent upon flow conditions and meter in use.



- A. Accuracy, %
- B. Flow rate, % of nominal

Turndown from nominal flow rate	40:1	15:1	2:1
Accuracy	0.26	0.10	0.10
Pressure drop	0.1 psig (0.007 barg)	0.45 psig (0.0310 barg)	14.2 psig (0.979 barg)

### Zero stability for all models

Model	Zero stability	
	lb/min	kg/h
H025	0.002	0.05
H050	0.012	0.32
H100	0.05	1.36
H200	0.16	4.35
H300	0.33	9.0

## Process pressure ratings

Sensor maximum working pressure reflects the highest possible pressure rating for a given sensor. Process connection type and environmental and process fluid temperatures may reduce the maximum rating. Refer to *Micro Motion H-Series Hygienic Coriolis Flow and Density Meters Technical Data Sheet* for common sensor and fitting combinations.

All sensors comply with Council Directive 2014/68/EU on pressure equipment.

### Sensor maximum working pressure for all models

Model	Pressure
H025F, H050F, H100F, H200F, H300F	1,015 psig (69.98 barg)
H025S, H050S, H100S, H200S, H300S	1,450 psig (99.97 barg)

## Case pressure

### Case pressure for all models

Model	Case maximum pressure	Typical burst pressure
H025	471 psig (32 barg)	1,884 psig (130 barg)
H050	383 psig (26 barg)	1,530 psig (105 barg)
H100	320 psig (22 barg)	1,281 psig (88 barg)
H200	190 psig (13 barg)	760 psig (52 barg)
H300	417 psig (29 barg)	1,668 psig (115 barg)

## Operating conditions: Environmental

### Vibration limits

Meets IEC 60068-2-6, endurance sweep, 5 to 2000 Hz, 50 sweep cycles at 1.0 g.

### Temperature limits


Sensors can be used in the process and ambient temperature ranges shown in the temperature limit graphs. For the purposes of selecting electronics options, temperature limit graphs should be used only as a general guide. If your process conditions are close to the gray area, consult with your Micro Motion representative.

#### Note

- In all cases, the electronics cannot be operated where the ambient temperature is below -40 °F (-40.0 °C) or above 140 °F (60.0 °C). If a sensor is to be used where the ambient temperature is outside of the range permissible for the electronics, the electronics must be remotely located where the ambient temperature is within the permissible range, as indicated by the shaded areas of the temperature limit graphs.
- Temperature limits may be further restricted by hazardous area approvals. Refer to the hazardous area approvals documentation shipped with the sensor or available from the *Micro Motion H-Series Hygienic Coriolis Flow and Density Meters Product Data Sheet*. For further questions, contact customer service.
- The extended-mount electronics option allows the sensor case to be insulated without covering the transmitter, core processor, or junction box, but does not affect temperature ratings. When insulating the sensor case at elevated process

temperatures (above 140 °F (60.0 °C)), please ensure electronics are not enclosed in insulation as this may lead to electronics failure.

**Ambient and process temperature limits for all H-Series meters**



## Operating conditions: Process

### Process temperature effect

- For mass flow measurement, process temperature effect is defined as the change in sensor flow accuracy due to process temperature change away from the calibration temperature. Temperature effect can be corrected by zeroing at the process conditions.
- For density measurement, process temperature effect is defined as the change in sensor density accuracy due to process temperature change away from the calibration density. See *Micro Motion H-Series Hygienic Coriolis Flow and Density Meters Installation Manual* for proper setup and configuration.

Model code	Mass flow rate (% of maximum rate)per °C	Density	
		g/cm <sup>3</sup> per °C	kg/m <sup>3</sup> per °C
H025, H050, H100, H200, H300	±0.0007	±0.0001	±0.1

### Process pressure effect

Process pressure effect is defined as the change in sensor flow and density accuracy due to process pressure change away from the calibration pressure. This effect can be corrected by dynamic pressure input or a fixed meter factor. See *Micro Motion H-Series Hygienic Coriolis Flow and Density Meters Installation Manual* for proper setup and configuration.



**Process pressure effect for all models**

Model code	Liquid or gas flow (% of rate)		Density	
	per psig	per barg	g/cm <sup>3</sup> per psig	kg/m <sup>3</sup> per barg
H025, H050, H100	none	none	none	none
H200	-0.001	0.015	-0.00003	-0.43
H300	-0.001	0.015	-0.00001	-0.145



# Hazardous area classifications

## Approvals and certifications

Type	Approval or certification (typical)	
CSA and CSA C-US	Ambient temperature: -40 °F (-40.0 °C) to 140 °F (60.0 °C) Class I, Div. 2, Groups A, B, C, and D Class II, Div.2, Groups F and G	
ATEX		II 1(2) G Ex ib IIB/IIC T6.T1 Ga/Gb II 2 D Ex ib IIIC T* °C Db IP66/IP67
		II 3G Ex nA IIC T1-T4/T5 Gc II 3D Ex tc IIIC T*°C Dc IP66
IECEX	Ex ib IIIC T* °C Db Ex nA IIC T1-T4/T5 Gc Ex tc IIIC T* °C Dc	
	Ex ib IIB/IIC T1-T4/T5/T6 Gb.  <b>Note</b> The H300 is Ex ib IIB; only with approval option code 7 it is Ex ib IIC.	
NEPSI	Ex ib IIB/IIC T1-T6 Gb Ex ibD 21 T450°C-T85°C Ex nA IIC T1-T6 Gc DIP A22 T* T1-T6	
Ingress Protection Rating	IP 66/67 for sensors and transmitters	
EMC effects	Complies with EMC directive 2004/108/EC per EN 61326 Industrial	
	Complies with NAMUR NE-21 (09.05.2012)	

**Note**

- Approvals shown are for H-Series meters. Meters with integral electronics may have more restrictive approvals. For details, refer to the transmitter Product Data Sheet.
- When a meter is ordered with hazardous area approvals, detailed information is shipped along with the product.
- More information about hazardous approvals, including detailed specifications and temperature graphs for all meter configurations is available on the H-Series product page at [www.emerson.com](http://www.emerson.com).

## Industry standards

Type	Standard
Weights and Measures for custody transfer applications:	<ul style="list-style-type: none"> <li>▪ National Type Evaluation Program (NTEP)</li> <li>▪ Measurement Canada</li> </ul>

Type	Standard
Industry standards and commercial approvals	<ul style="list-style-type: none"> <li>■ NAMUR: NE132 (burst pressure, sensor flange to flange length), NE131</li> <li>■ Pressure Equipment Directive (PED)</li> <li>■ Canadian Registration Number (CRN)</li> <li>■ Dual Seal</li> <li>■ ASME B31.3 Piping Code</li> <li>■ SIL2 and SIL3 safety certifications</li> </ul>
Hygienic approvals	<ul style="list-style-type: none"> <li>■ ASME BPE</li> <li>■ EHEDG, 3A</li> </ul>

## Transmitter interface

H-Series meters are highly customizable to provide a configuration that is tailor-fit to specific applications.

Robust transmitter offerings allow a multitude of mounting options:

- Compact mounting integral to the sensor
- Field mount variants for harsh conditions
- Compact control room DIN rail packages for optimal locating in a control cabinet
- Specific fit-for-purpose solutions for two-wire connectivity or filling and dosing machinery integration

H-Series meters are available with an expansive selection of input and output connectivity options including the following:

- 4-20 mA
- HART™
- WirelessHART™
- DeviceNet
- EtherNet/IP
- Profinet
- FOUNDATION™ fieldbus
- PROFIBUS
- Modbus®
- Other protocols may be available on request

## Physical specifications

### Materials of construction

General corrosion guidelines do not account for cyclical stress, and therefore should not be relied upon when choosing a wetted material for your Micro Motion meter. Please refer to the *Micro Motion Corrosion Guide* from the [www.emerson.com](http://www.emerson.com) site for material compatibility information.

**Wetted part materials**

Model	All models 316L stainless steel	Sensor weight
H025	•	13 lb (6 kg)
H050	•	15 lb (7 kg)
H100	•	23 lb (10 kg)
H200	•	42 lb (19 kg)
H300	•	105 lb (48 kg)

**Note**

- Weight specifications are based upon ASME B16.5 CL150 flange and do not include electronics.
- Heat jackets and steam kits are also available.

**Non-wetted part materials**

Component	Enclosure rating	316L/CF-3M stainless steel	304L stainless steel	Polyurethane-painted aluminum
Sensor housing	—		•	
Core processor housing	NEMA 4X (IP66/67)	•		•
Junction box housing	NEMA 4X (IP66)	•		•
Model 1700/2700 transmitter housing	NEMA 4X (IP66/69K)	•		•
Model 3700 transmitter housing	NEMA 4X (IP66/67)			•
Model 2400S transmitter housing	NEMA 4X (IP66/67/69K <sup>(1)</sup> )	•		•
Model 2200S transmitter housing	NEMA 4X (IP66/67)	•		•
Model 5700 transmitter housing	NEMA 4X (IP66/67/69K)	•		•

(1) Stainless steel version only.

**Flanges**

Sensor type	Flange types
All sensor models	<ul style="list-style-type: none"> <li>■ DIN11851, DIN11864-1A, DIN11864-2A, DIN11864-3A (up to DN80)</li> <li>■ IDF (Up to 3s)</li> <li>■ ISO 2853 (IDF) (DN76.1)</li> <li>■ Hygienic tri-clamp compatible</li> </ul>

**Note**

For more information about flange compatibility, contact customer support.

## Dimensions

These dimensional drawings are intended to provide a basic guideline for sizing and planning. They are representative of a sensor fitted with a Tri-clamp compatible flange and 2400 transmitter.


Face-to-Face (Dim. A, below) dimensions for all H-Series meters with each available process connection can be found in the H-series Technical Data Sheet.

For complete and detailed dimensional drawings, contact customer support.

### Note

- All dimensions are ±0.12 in (±3.0 mm)
- Representative of a sensor fitted with a Tri-clamp compatible flange and 2400 transmitter

### Example dimensions for all models



Model	Dim. A	Dim. B	Dim. C	Dim. D
H025	15.9 in (404 mm)	7.4 in (188 mm)	5.1 in (130 mm)	2.8 in (71 mm)
H050	17.4 in (442 mm)	7.4 in (188 mm)	6.7 in (170 mm)	3 in (76 mm)
H100	20.9 in (531 mm)	7.6 in (193 mm)	9.1 in (231 mm)	4.1 in (104 mm)
H200	21.3 in (541 mm)	8.5 in (216 mm)	12.6 in (320 mm)	5.6 in (142 mm)
H300	34.7 in (881 mm)	10.3 in (262 mm)	11.1 in (282 mm)	7.3 in (185 mm)

# Ordering information

## Model code structure

A complete sensor model code includes the ordering options.

Example code	Description
H	Sensor type
025	Model
S	<a href="#">Base model</a>
121	<a href="#">Process connections</a>
N	<a href="#">Case options</a>
C	<a href="#">Electronics interface</a>
A	<a href="#">Conduit connections</a>
A	<a href="#">Approvals</a>
E	<a href="#">Languages</a>
Z	<a href="#">Future option 1</a>
Z	<a href="#">Calibration</a>
Z	<a href="#">Factory options</a>
Z	<a href="#">Factory options</a>

## Base model

### Code descriptions

Codes S and F are model designations used to identify the type of meter.

Model	Material
S	316L stainless steel; 32 Ra finish (0.8 μm)
F	316L stainless steel; 15 Ra finish (0.4 μm)

### Codes available by model

Model	Available codes	
	F	S
H025 .25 in (DN6)	F	S
H050 .5 in (DN15)	F	S
H100 1 in (DN25)	F	S
H200 2 in (DN50)	F	S
H300 3 in (DN80)	F	S

## Process connections

### Model H025

Code	Description				
121	0.5 in (13 mm)	Tri-Clamp compatible	316L	Hygienic fitting	
222	DN15	DIN11851	316L	Hygienic coupling	
665	8A	IDF	316L	Hygienic fitting	Type CLF W
676	DN15	DIN11864-1A	316L	Aseptic connection	
C70	DN15	DIN11864-2A	316L	Hygienic flange	
C80	DN15	DIN11864-3A	316L	Hygienic flange	

### Model H050

Code	Description				
222	DN15	DIN11851	316L	Hygienic coupling	
322	0.75 in (19.0 mm)	Tri-Clamp compatible	316L	Hygienic fitting	
667	15A	IDF	316L	Hygienic fitting	Type CLF W
676	DN15	DIN11864-1A	316L	Aseptic connection	
C70	DN15	DIN11864-2A	316L	Hygienic flange	
C80	DN15	DIN11864-3A	316L	Hygienic flange	

### Model H100

Code	Description				
138	1 in (25 mm)	Tri-Clamp compatible	316L	Hygienic fitting	
230	DN25	DIN11851	316L	Hygienic coupling	
668	1s	IDF	316L	Hygienic fitting	Type CLF2 W
677	DN25	DIN11864-1A	316L	Aseptic connection	
C71	DN25	DIN11864-2A	316L	Hygienic flange	
C81	DN25	DIN11864-3A	316L	Hygienic flange	
C84	DN40	DIN11864-2A	316L	Hygienic flange	
C85	DN40	DIN11864-3A	316L	Hygienic flange	

**Model H200**

Code	Description				
352	2 in (51 mm)	Tri-Clamp compatible	316L	Hygienic fitting	
354	DN50	DIN11851	316L	Hygienic coupling	
669	2s	IDF	316L	Hygienic fitting	Type CLF2 W
678	DN50	DIN11864-1A	316L	Aseptic connection	
C68	DN50	DIN 1864-3A	316L	Hygienic flange	
C72	DN50	DIN 1864-2A	316L	Hygienic flange	

**Model H300**

Code	Description				
361	3 in (76 mm)	Tri-Clamp compatible	316L	Hygienic fitting	
664	DN76.1	ISO 2853 (IDF)	316L	Hygienic coupling	
679	DN80	DIN11864-1A	316L	Aseptic connection	
680	DN80	DIN11864-2A	316L	Aseptic connection	
685	DN80	DIN11851	316L	Hygienic coupling	
687	3s	IDF	316L	Hygienic fitting	Type CLF2 W
694	DN76	SMS 1145	316L	Hygienic coupling	
C69	DN80	DIN 1864-3A	316L	Hygienic flange	

**Case options****Case options (Models H015, H100, H200)**

Code	Case option
N	Standard case
P	Standard case with purge fittings (0.5 in (13 mm) NPT female)

**Case options (Model H300 only)**

Code	Case option
E	Enhanced case
F	3 in (76 mm) compact case retrofit installation (face-to-face extension mount)
P	Enhanced case with purge fittings (0.5 in (13 mm) NPT female)

## Electronics interface

### Code descriptions

Model	Description
0	For integral mount Model 2400S transmitter
1	For extended mount Model 2400S transmitter
2	4-wire polyurethane-painted aluminum integral enhanced core processor for remote mount transmitters
3 <sup>(1)</sup>	4-wire stainless steel integral enhanced core processor for remote mount transmitters
4	4-wire polyurethane-painted aluminum integral extended mount enhanced core processor for remote mount transmitters
5 <sup>(1)</sup>	4-wire extended mount stainless steel integral enhanced core processor for remote mount transmitters
6 <sup>(2)</sup>	MVDSolo; polyurethane-painted aluminum integral enhanced core processor (for OEMs)
7 <sup>(1)(2)</sup>	MVDSolo; stainless steel integral enhanced core processor (for OEMs)
8 <sup>(2)</sup>	MVDSolo; extended mount polyurethane-painted aluminum integral enhanced core processor (for OEMs)
9 <sup>(1)(2)</sup>	MVDSolo; extended mount stainless steel enhanced core processor (for OEMs)
Q	4-wire polyurethane-painted aluminum integral core processor for remotely mounted transmitters
A	4-wire stainless steel integral core processor for remotely mounted transmitters
C	For integral mount 1700/2700 transmitter
L <sup>(3)</sup>	For integral mount standard finish FMT transmitter
K <sup>(3)</sup>	For integral mount improved-surface finish (64 Ra [1.6 µm]) FMT transmitter
W <sup>(1)</sup>	MVDSolo; polyurethane-painted aluminum integral core processor for direct host connection (for OEMs)
D <sup>(1)</sup>	MVDSolo; stainless steel integral core processor for direct host connection (for OEMs)
R	9-wire polyurethane-painted aluminum junction box
H	9-wire extended mount polyurethane-painted aluminum junction box with

(1) Not available for truck mount.

(2) When electronics interface W, D, 6, 7, 8 or 9 is ordered with approval C, A, I, or Z, MVD Direct Connect™ I.S. barrier is supplied.

(3) Must be ordered with transmitter; only available with case code N.

### Codes available by model

Model	Available codes																		
	H	R	D	W	K	L	C	A	Q	9	8	7	6	5	4	3	2	1	0
H025, H050, H100	H	R	D	W	K	L	U	A	Q	9	8	7	6	5	4	3	2	1	0
H200, H300	H	R	D	W			U	A	Q	9	8	7	6	5	4	3	2	1	0

## Conduit connections

### Code descriptions

Code	Description
A	M20 — no gland



Code	Description
B <sup>(1)</sup>	0.5 in (13 mm) NPT – no gland
E	M20 – no gland; not available with electronics interface code Q, A, V, or B in combination with approval code T or S on models H200S-H300S
F <sup>(1)</sup>	Brass/nickel cable gland - cable diameter 0.335 in (8.51 mm) to 0.394 in (10.01 mm)
G <sup>(1)</sup>	Stainless steel cable gland - cable diameter 0.335 in (8.51 mm) to 0.394 in (10.01 mm)
H <sup>(1)</sup>	Brass/nickel cable gland
J <sup>(1)</sup>	Stainless steel cable gland
K <sup>(2)</sup>	JIS B0202 1/2G - no gland
L <sup>(2)</sup>	Japan - brass nickel gland
M <sup>(2)</sup>	Japan - stainless cable gland
N <sup>(2)</sup>	JIS B0202 3/4G - no gland
O <sup>(2)</sup>	Japan - brass nickel gland
p <sup>(2)</sup>	Japan - stainless cable gland

(1) Not available with approval T, S or J on models H200S and H300S.

(2) Only available with approval code M, T, or S.

**Codes available by model**

Model	Available codes													
	P	O	N	M	L	K	J	H	G	F	E	B	A	
All models with electronics interface codes 0, 1, C, K, and L													A	
All models with electronics interface codes 2, 3, 4, 5, Q, A, V, and B				M	L	K			G	F	E	B		
All models with electronics interface codes 6, 7, 8, 9, W, D, Y, and E									G	F	E	B		
All models with electronics interface codes R and H	P	O	N				J	H					A	

**Approvals**

**Code descriptions**

Code	Description
A	CSA (US and Canada): Class 1, Division 1
C	CSA (Canada only)
G	Country Specific Approval – Requires a selection from the Approvals section of the “Certificate, Tests, Calibrations and Services” model code option
I	IECEX Zone 1
J	Hardware ready for TIIS approval; EPM Japan only.
M	Micro Motion Standard; no approval; without CE/EAC markings

Code	Description
N	Micro Motion Standard / PED compliant; no approval; with CE/EAC markings
S	TIIS – T3 Temperature Classification; not available for quote outside of Japan
P	NEPSI
S	TIIS - T3 Temperature Classification; not available for quote outside of Japan
T	TIIS - T4 Temperature Classification; not available for quote outside of Japan
V	ATEX - Equipment Category 3 (Zone 2)
Z	ATEX - Equipment Category 2 (Zone 1) / PED compliant
2	CSA (US and Canada): Class 1, Division 2
3	IECEX Zone 2

**Codes available by model**

Model	Codes Available													
	3	2	Z	V	T	S	N	M	J	I	G	C	A	
All models with electronics code 0, 1, L, and K	3	2		V			N	M			G			
All models with electronics code Q, A, V, B, C, R, and H			Z		T	S	N	M	J	I	G	C	A	
All models with electronics code 6, 7, 8, 9, W, D, Y, and E			Z				N	M		I	G	C	A	
All models with electronics code 2, 3, 4, and 5			Z				N	M		I	G		A	

**Languages**

Code	Language option
A	Danish CE requirements document and English installation manual
C	Czech installation manual
D	Dutch CE requirements document and English installation manual
E	English installation manual
F	French installation manual
G	German installation manual
H	Finnish CE requirements document and English installation manual
I	Italian installation manual
J	Japanese installation manual
M	Chinese installation manual
N	Norwegian CE requirements document and English installation manual
O	Polish installation manual

Code	Language option
P	Portuguese installation manual
S	Spanish installation manual
W	Swedish CE requirements document and English installation manual
B	Hungarian CE requirements document and English installation manual
K	Slovak CE requirements document and English installation manual
T	Estonian CE requirements document and English installation manual
U	Greek CE requirements document and English installation manual
L	Latvian CE requirements document and English installation manual
V	Lithuanian CE requirements document and English installation manual
Y	Slovenian CE requirements document and English installation manual

## Future option 1

Code	Future option 1
Z	For models H025F, H050F, H100F, H200F, H300F; reserved for future use

## Calibration

Code	Calibration option
Z	0.15% mass flow, 0.25% volume flow, and 0.002 g/cm <sup>3</sup> (2 kg/m <sup>3</sup> ) density calibration
1	0.10% mass flow, 0.15% volume flow, and 0.001 g/cm <sup>3</sup> (1 kg/m <sup>3</sup> ) density calibration
K	0.10% mass flow, 0.15% volume flow, and 0.0005 g/cm <sup>3</sup> (0.5 kg/m <sup>3</sup> ) density calibration <sup>(1)(2)</sup>

(1) Only available with electronics code 0, 1, 2, 3, 4, 5, 6, 7, 8, 9.

(2) Not available with model H025.

## Measurement application software

Code	Factory options
Z	No measurement application software

## Factory options

Code	Factory option
Z	Standard product
X	ETO product
R	Restocked product if available

## Certificates, tests, calibrations, and services

### Certificates, tests, calibrations, and services

These option codes can be added to the end of the model code if needed, but no code is required when none of these options is selected.

#### Note

There may be additional options or limitations depending on total meter configuration. Contact a sales representative before making your final selections.

### Material quality examination tests and certificates

Select any from this group.

Code	Factory option
MC	Material inspection certificate 3.1 (supplier lot traceability per EN 10204)
NC	NACE certificate 2.1 (MR0175 and MR0103)

### Radiographic testing

Select only one from this group.

Code	Factory option
RE	X-ray package 3.1 (radiographic examination certificate; weld map; radiographic inspection NDE qualification)
RT	X-ray package 3.1 (radiographic examination certificate with digital image; weld map; radiographic inspection NDE qualification)

### Pressure testing

Code	Factory option
HT	Hydrostatic test certificate 3.1

### Dye penetrant examination

Code	Factory option
D1	Dye penetrant test package 3.1 (Liquid Dye Penetration NDE Qualification): <ul style="list-style-type: none"> <li>■ Sensor only (H025-H200)</li> <li>■ Sensor process connection only (H300)</li> </ul>

### Weld examination

Code	Factory option
WP	Weld procedure package (weld map, weld procedure specification, weld procedure qualification record, welder performance qualification)

### Positive material testing

Select only one from this group.

Code	Factory option
PM	Positive material test certificate 3.1 without carbon content
PC	Positive material test certificate 3.1 including carbon content

**Special cleaning**

Code	Factory option
O2	Declaration of compliance oxygen service 2.1

**GOST compliance**

Code	Factory option
GR	Russian GOST calibration verification certificate

**Accredited calibration**

Code	Factory option
IC	ISO17025 accredited calibration and certificates (9 points total)

**Special calibration options**

Select either none, CV, or CV with one of the additional verification point options.

**Note**

For all special calibration options, the minimum flow rate for any verification point is 5% of sensor nominal flow rate.

Code	Factory option
CV	Custom verification (alter original verification points)
01	Add 1 additional verification point
02	Add 2 additional verification point
03	Add 3 additional verification point
06	Add up to 6 additional verification points
08	Add up to 8 additional verification points
16	Add up to 16 additional verification points

**Sensor completion options**

Select any from this group.

Code	Factory option
WG	Witness general
SP	Special packaging

**Country specific approvals**

Select one from the following if approval code G is selected.

Code	Factory option
R1	EAC Zone 1 – Hazardous Approval <sup>(1)(2)</sup>
R3	EAC Zone 2 – Hazardous Approval <sup>(1)(3)</sup>
B1	INMETRO Zone 1 – Hazardous Approval <sup>(1)(2)</sup>
B3	INMETRO Zone 2 – Hazardous Approval <sup>(1)(3)</sup>

(1) Only available with approval code G.

(2) Not available with electronics code 0, 1, K, or L.

(3) Only available with electronics code 0, 1, K, and L.